



25	KX06-198E-19A	Gland Nut	1	CZ121	
24	KX06-045B-105	Lock &Key	1		
23	KX06-009N-09-01	Leather chain	1	leather	
22	KX06-198A-52	Cover	1	CZ121	
21	KX06-198A-81	Gland Nut	1	CZ122	
20	KX06-198A-43	Lug pull	1	CZ122	
19	KX06-198A-80	Release bolt	1	CZ122	
18	KX06-009-24	Pin	2	SS304	
17	KX08-087-11	Spring	1	SS304	
16	KX08-021-34	Nut	1	BS-1C22	
15	KX08-201A-37	Seal	1	Natural rubber	
14	KX06-032-09	Chain	1	SS304	
13	KX08-024B2-78	cap	1	LM25	
12	KX06-009-43	Handwheel	1	GRAY CAST IRON 180	
11	KX06-009E-20B	Washer	1	6063	
10	KX06-198E-10	O-ring	2	NBR	
9	KX06-198E-74-J	Bonnet	1	CZ122	
8	KX06-174-10	O-ring	1	NBR	
7	KX06-198E-02-04	Stem	1	CZ121	
6	KX06-198E-19	Gland Nut	1	CZ122	
5	KX06-198E-39	Disk	1	CZ122	
4	KX06-060-37	DISK FACING	1	NBR	
3	KX06-060-20	Spacer	1	304	
2	KX06-009-34B	Locknut	2	304	
1	KX06-200E-01-J	Body & outlet	1	LG2	
NO.	PART NO.	PART NAME	QTY	MATERIAL	

Technical requirements:

- 1, the product according to BS 5041-1:1987 design.
- 2.The landing valves are suitable for continuous use at 15bar pressure rating throughout temp range from 0℃ to 38℃
- 3.Seal test: the test pressure 16.5bar, the test medium:water,holding pressure 2 minutes.
- 4.Body strength test: the test pressure 22.5bar, the test medium:water,holding pressure 2 minutes
- 5, Water flow rate test: Control valves to give a flow rate of 8.5L/min, Out pressure ≥4bar when inlet pressure 4.7bar.
- 6.The number of turns 4~10
- 7, Body thickness ≥3mm
- 8, All o-rings,washers are hansheng procurement.
- 9, Bronze color

MARKING	QTY	FRLE NO	NAMES	DATES	HORIZONTAL LANDING VALVE	QTY	1	
INITIAL			NAMES	DATES		DRAWING MARKING	WEIGHT	SCALE
DESIGNED			He weiqiong				4.64Kg	1:1.5
CHECKED								
APPROVED					MATERIAL			